

	Rated input voltage	voltage range	power rating	real power	real luminous flux	rendering index	color temp
PSL- 4U/ 125W R	220- 240V	170- 265V	125W	85- 95w	>5600l m		80 2700k
PSL- 4U/ 125W B	220- 240V	170- 265V	125W	85- 95w	>5500l m		80 6400k
PSL-4U/125W.P	220-240V	170-265V	125W	85-95W			80 PURPLE
PSL- 4U/ 125W D	220- 240V	170- 265V	125W	85- 95w	>5500l m		80 2700/ 6400K
PSL- 4U/ 85W R	220- 240V	170- 265V	85W	65- 75W	>4600l m		80 2700k
PSL- 4U/ 85W B	220- 240V	170- 265V	85W	65- 75W	>4500l m		80 6400k
PSL-4U/85W.P	220-240V	170-265V	85W	65-75W			PURPLE
PSL- 4U/ 85W D	220- 240V	170- 265V	85W	65- 75W	>4600l m		80 2700/ 6400K
PSL- 5U/ 125W R	220- 240V	170- 265V	125W	95- 105W	>6300l m		80 2700k
PSL- 5U/ 125W B	220- 240V	170- 265V	125W	95- 105W	>6300l m		80 6400k
PSL-5U/125W.P	220-240V	170-265V	125W	95-105W			PURPLE
PSL- 6U/ 200W R	220- 240V	170- 265V	200W	145- 165W	>9000l m		80 2700k
PSL- 6U/ 200W B	220- 240V	170- 265V	200W	145- 165W	>9000l m		80 6400k
PSL-6U/200W.P	220-240V	170-265V	200W	145-165W			PURPLE
PSL- 6U/ 200W D	220- 240V	170- 265V	200W	145- 165W	>9000l m		80 2700/ 6400K
PSL- 8U/ 250W R	220- 240V	170- 265V	250W	175- 190W	>11000l m		80 2700k
PSL- 8U/ 250W B	220- 240V	170- 265V	250W	175- 190W	>11000l m		80 6400k
PSL-8U/250W.P	220-240V	170-265V	250W	175-190W			PURPLE
PSL- 8U/ 250W D	220- 240V	170- 265V	250W	175- 190W	>11000l m		80 2700/ 6400K

R: RED, B: BLUE, P: PURPLE, D: DOUBLE
SPECTRUM ANALYZER