

# Bluelab Product Information Sheet

for Distributors of Bluelab Nutrient Solution Testers and Accessories

<b>Product Name:</b>	<b>Bluelab Truncheon® Nutrient Meter V2</b>
<b>Product Code:</b>	<b>TRUNV2</b>
<b>UPC Code:</b>	9421024920012
<b>Country of Origin:</b>	New Zealand
<b>Tariff Code:</b>	9027.80
<b>Shipping Quantity:</b>	10 kg = 56 units / 25 kg = 135 units
<b>Packaging Information:</b>	
<b>Packaged Weight:</b>	0.28 kg / 0.617 lb
<b>Packaged Length:</b>	415 mm / 16.34 in
<b>Packaged Width:</b>	40 mm / 1.574 in
<b>Packaged Height:</b>	40 mm / 1.574 in

## Sales Description:

*NOTE: this copy can be used in brochures, catalogues or online*

### The world's favourite conductivity meter. Simply brilliant, brilliantly simple!

It is essential when growing with a hydroponic solution to KNOW what the strength of the solution is before feeding your plants AND while they are growing.

This is easy if you use the Bluelab Truncheon® Nutrient Meter! To take a reading of your solution - simply place the probe head into the solution for 1-2 minutes to reach the same temperature of your nutrient. The reading is indicated by the flashing lights. Calibration of the Meter is not required.

Meter length: 40.7cm or 16 1/32 in.

## Features:

- Fully waterproof
- Auto on/off function
- No calibration required
- Daylight readable blue LED's
- Battery operated
- No buttons, switches or knobs
- Provided with EC, CF, ppm 700 and ppm 500 scales

A version is available with Canadian French-English product labelling and packaging. Product details are:

**Name:** Bluelab Truncheon® Nutrient Meter French-English V2

**Product code:** TRUNFV2

**UPC Code:** 9421024920142.

*Images available on request.*

## Product Image:



## Product images available for Screen or Web use:

- Bluelab-Truncheon2-R-MR-flat-RGB.jpg
- Bluelab-Truncheon2-R-WEB.jpg
- Bluelab-Truncheon2-R-Web-Sml.jpg

## Product images available for PRINT:

*Note: these images are high resolution in CMYK.*

- Bluelab-Truncheon2-R-MR-flat-CMYK.tif

## Technical Specifications:

<b>Measurement Range:</b>	0.2 – 3.6 EC, 2 – 36 CF 100 – 1800 ppm (EC x 500) 140 – 2520 ppm (EC x 700)
<b>Resolution:</b>	0.1 EC, 1 CF 50 ppm (EC x 500) 70 ppm (EC x 700)
<b>Accuracy at 2.77EC and 25°C / 77°F:</b>	± 0.1 EC, ± 1 CF ± 50 ppm (1385 ppm at 500 ppm) ± 70 ppm (1939 ppm at 700 ppm)
<b>Automatic Temperature Compensation:</b>	Yes
<b>Operating Environment:</b>	0 – 50°C / 32 – 122°F
<b>Calibration:</b>	Not required
<b>Power Source:</b>	3 x AA alkaline batteries
<b>User Manual Languages Available:</b>	English; Español; Français-Canada; Nederlands; Deutsch
<b>Certifications:</b>	CE and FCC

## Product Guarantee:

Five year free repair or replacement guarantee.

