

Bluelab Product Information Sheet

for Distributors of Bluelab Nutrient Solution Testers and Accessories

Product Name:	Bluelab EC Pen
Product Code:	PENEC
UPC Code:	9421024920210
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	10 kg = 100 units / 25 kg = 230 units
Packaging Information:	
Packaged Weight:	0.13 kg / 0.287 lb
Packaged Length:	205 mm / 8.07 in
Packaged Width:	55 mm / 2.165 in
Packaged Height:	32 mm / 1.26 in

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

The ultimate handy solution for measuring conductivity!

The Bluelab EC Pen is the latest innovation for hand held conductivity meters. It provides a compact, quick and handy way to manage the success of your crops.

The Bluelab EC Pen simply tells you that your plants have the right amount of nutrient in your solution and lets you know if adjustments are needed.

Display options available in °C, °F, EC, CF, ppm 500 and ppm 700.

Teamed with our Bluelab pH Pen, you have a handy, convenient and accurate system for ensuring optimum plant growth and health.

Now, isn't that handy?

Features:

- Measures conductivity and temperature
- Selectable units for conductivity and temperature
- Backlit LCD display
- Calibration optional
- Successful calibration indicator
- Hold reading function
- Low battery indicator
- Fully waterproof
- Auto off function
- Automatic temperature compensation

Product Guarantee:

One year free repair or replacement guarantee.



Product Image:



Product images available for Screen or Web use:

- Bluelab-ECPen-MR-flat-RGB.jpg
- Bluelab-ECPen-WEB.jpg
- Bluelab-ECPen-Web-sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-ECPen-MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.0 – 10.0 EC 0 – 5000 ppm (500 ppm / TDS) 0 – 7000 ppm (700 ppm) 0 – 50 °C / 32 – 122 °F
Resolution:	0.1 EC 10 ppm (500 ppm) 10 ppm (700 ppm) 1 °C / 1 °F
Accuracy at 2.77 EC and 25 °C / 77 °F:	± 0.1 EC ± 50 ppm (500 ppm) ± 70 ppm (700 ppm) ± 1 °C / ± 2 °F
Automatic Temperature Compensation:	Yes
Operating Environment:	0 – 50 °C / 32 – 122 °F
Calibration:	Optional
Power Source:	1 x AAA alkaline battery
User Manual Languages Available:	English; Español; Français; Nederlands; Deutsch
Certifications:	CE and FCC