

Bluelab Product Information Sheet

for Distributors of Bluelab Nutrient Solution Testers and Accessories

Product Name:	Bluelab Combo Meter
Product Code:	METCOM
UPC Code:	9421024920036
Country of Origin:	New Zealand
Tariff Code:	9027.80
Shipping Quantity:	10 kg = 21 units / 25 kg = 50 units
Packaging Information:	
Packaged Weight:	0.48 kg / 1.06 lb
Packaged Length:	180 mm / 7.086 in
Packaged Width:	110 mm / 4.33 in
Packaged Height:	83 mm / 3.267 in

Sales Description:

NOTE: this copy can be used in brochures, catalogues or online

It's all you need for simple and reliable crop management and it's all within arm's reach!

The Bluelab Combo Meter is a pH, conductivity and temperature meter all in one.

The Bluelab pH Probe and the Bluelab Conductivity/Temperature Probe are simply placed into the solution and the selected reading is displayed on screen.

As the Bluelab Combo Meter is portable and does not require a power supply to operate, it can be used anytime and anywhere to help you manage your crops daily nutrient requirements.

Calibration of the pH is simple with the push buttons on the meter and fresh calibration solutions. Conductivity and temperature do not need to be calibrated as this is locked in during manufacture.

Features:

- Measures pH, conductivity / nutrient (EC, CF, ppm 500 and ppm 700) and temperature (°C, °F)
- Lightweight and portable
- Large easy to read display
- Simple push button pH calibration
- Successful pH calibration indicator
- No calibration required for conductivity and temperature
- Replaceable double junction pH probe
- Over range and under range indicators
- Low battery indicator
- 2 x AAA alkaline batteries included
- Auto off function

Product Guarantee:

Five year free repair or replacement guarantee.
* Six months for pH Probe.



Product Image:



Product images available for Screen or Web use:

- Bluelab-ComboMeter-MR-flat-RGB.jpg
- Bluelab-ComboMeter-WEB.jpg
- Bluelab-ComboMeter-Web-sml.jpg

Product images available for PRINT:

Note: these images are high resolution in CMYK.

- Bluelab-ComboMeter-MR-flat-CMYK.tif

Technical Specifications:

Measurement Range:	0.0 – 14.0 pH, 0.0 – 9.9 EC, 99 CF 0 – 4950 ppm 500 (EC x 500) 0 – 6930 ppm 700 (EC x 700) 0 – 50 °C / 32 – 122 °F
Resolution:	0.1 pH, 0.1 EC, 1 CF 10 ppm 500, 10 ppm 700 1 °C / 1 °F
Accuracy at 2.77 EC and 25°C / 77°F:	± 0.1 pH, ± 1 EC, ± 1 CF, ± 50 ppm 500, ± 70 ppm 700 ± 1 °C / ± 2 °F
Automatic Temperature Compensation:	Yes
Operating Environment:	0 – 50 °C / 32 – 122 °F
Calibration:	Not required for conductivity. pH requires two point, pH 7.0 & pH 4.0 or pH 10.0 calibration
Power Source:	2 x AAA alkaline batteries
User Manual Languages Available:	English; Español; Français; Nederlands; Deutsch
Certifications:	CE and FCC